



## 480 and 485 EZ WALL MOUNTED DRINKING FOUNTAIN SPECIFICATIONS

### WATER QUALITY (LEAD FREE)

Section 9, California Proposition 6 and the Federal Safe Drinking Water Act.

### STANDARD WALL MOUNT

One piece weld construction with MDF standard 3/16" wall thickness

OR

### STAINLESS STEEL WALL MOUNT

One piece weld construction with MDF standard 304 schedule 10 stainless steel

### RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal, preventing buildup of residue in visual drinking area. Optional stainless steel Bowl Strainer recommended for areas with sand.

### BUBBLER HEAD

Stainless steel anti-squirt head (weighing a pound and a half) mounted with a lock nut and washer to prevent tampering. Lock nut pin holds bubbler in locked position to prevent twisting or turning. The MDF bubbler head has a unique design that features a steady stream trajectory and a built in natural shield from contamination. (Most Dependable Fountains, Inc.™ encourages bubbler comparison.)

### PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

### CONTROL VALVE

Requires less than 5 lbs to operate. Non-cartridge O-ring valve delivers steady stream of water through an adjustable valve. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

### WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing - **this tubing is not plastic**. It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection.

### FINISH

Oven baked powder coat. Choice of colors are:  green,  blue,  black,  brown,  red,  yellow,  orange and  white. Textured color choices:  emerald,  sapphire,  pyrite,  text-black,  burgandy,  gold vein,  copper and  sandstone. Stainless steel models are powder coated for added protection. The color  chrome is available for stainless steel models only.

### WASTE

Y DRAIN

### ACCESS

Working parts accessible through bowl of fountain for easy service.

### INSTALLATION

The EZ Wall Mounted drinking fountain is furnished with a wall carrier plate to be anchored to a finished wall.

### WINTERIZATION

Shut off water and drain down.

### WARRANTY

One year warranty, labor not included.

### SHIPPING WEIGHT

Model 480 EZWM..... 40 lbs    Model 480 EZWMSS..... 40 lbs  
Model 485 EZWM..... 95 lbs    Model 485 EZWMSS..... 95lbs

**MOST DEPENDABLE FOUNTAINS, INC.™**  
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
www.mostdependable.com  
(901)867-0039

