



BIKE STAND SERIES SPECIFICATIONS

- STANDARD PEDESTAL
- OR
- STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

INSTALLATION

Surface Mount installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the station. Surface mount carrier recommended for all surface mount installations.

FINISH

The sixteen powder coat colors listed are at no additional charge. The colors are: green, blue, brown, black, red, yellow, orange, white and textured emerald, textured sapphire, textured pyrite, textured black, textured burgandy, textured gold vein, textured copper and textured sandstone. Stainless steel fountains are powder coated for added protection. The color chrome is available for stainless steel models only.

WARRANTY

One year warranty, labor not included.

SHIPPING WEIGHT

Model 210 SM..... 30 lbs	Model 225 SM..... 28 lbs	Model 250 SM..... 40 lbs
Model 210 SMSS... 30 lbs	Model 225 SMSS... 28 lbs	Model 250 SMSS... 40 lbs

MOST DEPENDABLE FOUNTAINS, INC.™
 (800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

