



MDF 40018 CHILLED SERIES DRINKING FOUNTAIN SPECIFICATIONS

WATER QUALITY (LEAD FREE)

Lead free by all known definitions including ANSI/NSF standard 61,

Section 9, California Proposition 6 and the Federal Safe Drinking Water Act.

STANDARD PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness

OR

STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel

RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal, preventing build-up of residue in visual drinking area. Optional SS Bowl Strainer recommended for areas with sand.

BUBBLER HEAD

Stainless steel anti-squirt head (weighing a pound and a half) mounted with lock nut and washer to prevent tampering. Lock nut pin holds bubbler in locked position to prevent twisting or turning. The MDF bubbler head's unique design features a constant steady stream trajectory and a built in natural shield from contamination. (Most Dependable Fountains, Inc.™ encourages bubbler comparison)

PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel housing standard on both standard and stainless steel pedestals.

CONTROL VALVE

Requires less than 5 lbs. to operate. Non-cartridge O-ring valve delivers steady stream of water through flow regulator. No adjustment necessary. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

WATER SUPPLY (LEAD FREE)

Maintenance-free reinforced nylobraid tubing and fittings, NSF-61 certified. This tubing is not plastic. Supplied with a 1/2" MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

FINISH

The sixteen powder coat colors listed are at no additional charge. The colors are: green, blue, brown, black, red, yellow, orange, white and textured emerald, sapphire, pyrite, black, burgundy, gold vein, copper and sandstone. Stainless steel fountains are powder coated for added protection and all colors listed are available.

ACCESS

Working parts accessible through bowl of fountain for easy service. Supply and waste connections are through the above grade access door. All access plates, brackets, vandal resistant bolts and screws are stainless steel.

INSTALLATION

Surface Mount fountains anchor to a concrete pad through a welded mounting plate. SS surface carriers recommended for all new installations. Flush all new or existing supply lines prior to installation.

CHILLER and WINTERIZATION

Chilling capacity 8 gallons per hour. NO lead design. 115 VAC. Shut off water and drain down. Remove chiller if applicable.

WARRANTY

One year warranty. Labor not included.

SHIPPING WEIGHTS

Model 40018 SM..... 210 lbs. Model 44018SM* 265 lbs. Model 40018 SMSS 210 lbs.
Model 44018 SMSS* 265 lbs. Model 41018 SM..... 210 lbs. Model 493 SM* 295 lbs.
Model 41018 SMSS 210 lbs. Model 493 SMSS* 295 lbs.

*meets ADA for High and Low

NOTE: When ordering, please specify stainless steel by SS. Always note your color choice and options where applicable. (Options added at an additional cost to the customer.) Example: Specify 44018 SMSS to order 44018 Surface Mount Stainless Steel. Please call MDF to assist you with ordering, quoting and shipping.

MOST DEPENDABLE FOUNTAINS, INC.™
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

