



505 SM RINSE STATION SPECIFICATIONS

■ STANDARD PEDESTAL

OR

■ STAINLESS STEEL PEDESTAL

PUSH BAR

One piece weld construction with MDF standard 3/16" wall thickness OR

One piece weld construction with MDF standard 304 schedule 10 stainless steel. 304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel housing standard on both standard and stainless steel pedestals.

HOSE BIBB CONNECTION

Stainless steel with standard hose connection.

VALVE

1/2" metered valve with 30-45 second run time.

WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing that is NSF-61 certified. **This tubing is not plastic.** It is supplied with a 1/2" MIP threaded inlet with a stainless steel strainer. Union fittings at every connection. Supply line stops above grade. Includes inline vacuum breaker.

FINISH

The sixteen powder coat colors listed are at no additional charge. The colors are: green, blue, brown, black, red, yellow, orange, white and textured emerald, textured sapphire, textured pyrite, textured black, textured burgandy, textured gold vein, textured copper and textured sandstone. The color chrome is available for stainless steel models only.

INSTALLATION

Surface Mount installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the station. Surface Mount Stations provide an access door with vandal resistant stainless steel screws. Surface mount carrier recommended for all surface mount installations.

WINTERIZATION

Shut off water and drain down. Remove valve during winter months.

WARRANTY

One year warranty, labor not included.

MOST DEPENDABLE FOUNTAINS, INC.™
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com

