



# 400 SERIES WALL MOUNTED DRINKING FOUNTAIN SPECIFICATIONS

## WATER QUALITY (LEAD FREE)

Section 9, California Proposition 6 and the Federal Safe Drinking Water Act.

## STANDARD PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

OR

## STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

## RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal, preventing buildup of residue in visual drinking area. Optional stainless steel Bowl Strainer recommended for areas with sand.

## BUBBLER HEAD

Stainless steel anti-squirt head (weighing a pound and a half) mounted with a lock nut and washer to prevent tampering. Lock nut pin holds bubbler in locked position to prevent twisting or turning. The MDF bubbler head has a unique design that features a steady stream trajectory and a built in natural shield from contamination.

## PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

## CONTROL VALVE

Requires less than 5 lbs to operate. Non-cartridge O-ring valve delivers steady stream of water through an adjustable valve. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

## WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing that is NSF-61 certified. **This tubing is not plastic.** It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection.

## FINISH

Oven baked powder coat. Choice of colors are:  green,  blue,  black,  red,  yellow,  orange,  brown and  white. Textured color choices:  emerald,  sapphire,  pyrite,  text-black,  burgundy,  gold vein,  copper and  sand-stone. Stainless steel models are powder coated for added protection. The color  chrome is available for stainless steel models only.

## INSTALLATION

The Wall Mounted drinking fountain is designed to be anchored to a wall (concrete, masonry, etc.) with anchor bolts through a mounting plate that is welded to the fountain. MDF offers standard wall mount and pedestal wall mount drinking fountains. An optional stainless steel carrier is recommended for all standard wall mounts. The pedestal wall mount is flush with the ground and bolted to the wall. The pedestal wall mount works extremely well when specified for remodeling.

## WINTERIZATION

Shut off water and drain down.

## WARRANTY

One year warranty, labor not included.

## SHIPPING WEIGHT

Model 450 WM..... 30 lbs.	Model 450 WMSS..... 30 lbs.	Model 450 Carrier... 25 lbs.
Model 475 WM..... 95 lbs.	Model 475 WMSS*.... 95 lbs.	Model 475 Carrier... 50 lbs
Model 410 WM..... 85 lbs.	Model 410 WMSS..... 85 lbs.	
Model 440 WM* .. 135 lbs.	Model 440 WMSS*.. 135 lbs.	

**MOST DEPENDABLE FOUNTAINS, INC.™**  
 (800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)

