Jug Filler Specifications

☐ STANDARD PEDESTAL

OR

☐ STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

CONTROL VALVE

Requires less than 5 lbs to operate. Non-cartridge O-ring valve delivers steady stream of water. No adjustment necessary. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

INSTALLATION

Surface Mount installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the unit. Surface mount carrier recommended for all surface mount installations. Flush all new or existing supply lines prior to installation. 10" bury in ground for **Direct Bury** models. All direct bury models have an attached valve box with bolted cover included.

FINISH

Oven baked powder coat color choices:

☐ Green, ☐ Blue, ☐ Black, ☐ Red, ☐ Brown, ☐ White, ☐ Teal, ☐ Umbria Grey

Textured color choices:

☐ Emerald, ☐ Sapphire, ☐ Textured Black, ☐ Pyrite, ☐ Sandstone, ☐ Gold Vein, ☐ Copper

The color CHROME is an available option for Stainless Steel (SS) models only.

☐ Chrome

Stainless steel models are powder coated for added protection.

WINTERIZATION

Shut off water and drain down. Remove valve during winter months.

WARRANTY

One year warranty, labor not included.

SHIPPING WEIGHT

Model 125 SM ..... 51 lbs
Model 125 SMSS ..... 51 lbs
Model 125 WMSSJF..... 20 lbs

MOST DEPENDABLE FOUNTAINS, INC™

5705 Commander Dr.
Arlington, TN 38002

mostdependable.com
(901) 867-0039