



HAND WASH SPECIFICATIONS

WATER QUALITY (LEAD FREE)

Section 9, California Proposition 6 and the Federal Safe Drinking Water Act. One piece weld construction with MDF standard 3/16" wall thickness.

STANDARD PEDESTAL

OR

STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

RECEPTOR BOWL

18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal, preventing build-up of residue in visual drinking area. Optional stainless steel Bowl Strainer recommended for areas with sand.

METERED FAUCET

Automatic shut-off with vandal resistant handle. 10 second flow cycle. Water conserving 0.5 gpm. Self closing valve requires less than 5 lbs. to operate. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

OR

SENSOR

Motion activated.

OPTIONAL HAND SOAP

When applicable:

Dispenser - Stainless steel dispenser with vandal resistant bolts & screws.

Hand Soap - Alcohol Free - Foaming Instant Hand Soap is confirmed to reduce harmful bacteria by 99.99%.

WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing - **this tubing is not plastic**. It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

DRAIN

1 1/2" schedule 40 PVC pipe. Drain line stops above grade.

FINISH

Oven baked powder coat. Choice of colors are: green, blue, black, brown, red, yellow, orange, and white. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection. The color chrome is available for stainless steel models only.

ACCESS

Working parts accessible through bowl of fountain for easy service. Supply and waste connections are through the above grade access door. All access plates, brackets, vandal resistant bolts and screws are stainless steel.

INSTALLATION

Surface Mount installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount Fountains provide an access door with vandal resistant stainless steel screws. Surface mount carrier recommended for all surface mount installations. Access door standard on all pedestal fountains. **EZ Wall Mount** installations will be furnished with a wall carrier plate to be anchored to a finished wall.

WINTERIZATION

Shut off water and drain down.

WARRANTY

One year warranty, labor not included.

SHIPPING WEIGHT

| | | | | |
|------------|--------------|--------------|--------------|---------------------------|
| 600 SM* | ... 115 lbs. | 600 SMSS* | ... 115 lbs. | *Meets ADA for High & Low |
| 600 EZ WM* | ... 50 lbs. | 600 EZ WMSS* | ... 50 lbs. | |

Sensor:

| | | | |
|---------------|--------------|-----------------|--------------|
| SE 600 SM* | ... 115 lbs. | SE 600 SMSS* | ... 115 lbs. |
| SE 600 EZ WM* | ... 50 lbs. | SE 600 EZ WMSS* | ... 50 lbs. |

MOST DEPENDABLE FOUNTAINS, INC.™

5705 COMMANDER DR. • ARLINGTON, TN 38002-0587

www.mostdependable.com

(901) 867-0039