Most Dependable Fountains, Inc.


OPERATIONS MANUAL

MODEL: SE 600 EZ WM & SE 600 EZ WMSS

Most Dependable Fountains, Inc™ 5705 Commander Drive Arlington, TN 38002 901-867-0039 www.mostdependable.com



MOST DEPENDABLE FOUNTAINS, INC. 5705 COMMANDER DR. P.O. BOX 587 ARLINGTON, TN 38002-0587 PHONE: (901) 867-0039 www.mostdependable.com



SIDE VIEW

FRONT VIEW

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. NOTE TO ARCHITECT, SCALE DRAWING IN AUTOCAD MODEL SPACE.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 3354-14.13

SE 600 EZWM

PROTECTED BY COPYRIGHT ©2021 CADDETAILS.COM LTD.

3354-14.13

CADdetailsPLUS™

REVISION DATE 08/02/2021



MOF HAND WASH SPECIFICATIONS

WATER QUALITY (LEAD FREE)	Section 9, California Proposition 6 and the Federal Safe Drinking Water Act. One piece weld construction with MDF standard 3/16" wall thickness.
OR STAINLESS STEEL PEDESTAL	One piece weld construction with MDF standard 304 schedule 10 stainless steel.
RECEPTOR BOWL	18 gauge electro-polished stainless steel bowl. Bowl overlaps pedestal, preventing build-up of residue in visual drinking area. Optional stainless steel Bowl Strainer recommended for areas with sand.
■ METERED FAUCET OR	Automatic shut-off with vandal resistant handle. 10 second flow cycle. Water conserving 0.5 gpm. Self closing valve requires less than 5 lbs. to operate. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.
SENSOR	Motion activated.
OPTIONAL HAND SOAP	When applicable: Dispenser - Stainless steel dispenser with vandal resistant bolts & screws. Hand Soap - Alcohol Free - Foaming Instant Hand Soap is confirmed to reduce harmful bacteria by 99.99%.
WATER SUPPLY (LEAD FREE)	Maintenance free reinforced nylobraid tubing - this tubing is not plastic . It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection. Supply line stops above grade.
DRAIN	1 1/2" schedule 40 PVC pipe. Drain line stops above grade.
FINISH	Oven baked powder coat. Choice of colors are: green, blue, blue, black, brown, red, yellow, orange, and white. Textured color choices: merald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection. The color chrome is available for stainless steel models only.
ACCESS	Working parts accessible through bowl of fountain for easy service. Supply and waste connections are through the above grade access door. All access plates, brackets, vandal resistant bolts and screws are stainless steel.
INSTALLATION	Surface Mount installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the fountain. Surface Mount Fountains provide an access door with vandal resistant stainless steel screws. Surface mount carrier recommended for all surface mount installations. Access door standard on all pedestal fountains. EZ Wall Mount installations will be furnished with a wall carrier plate to be anchored to a finished wall.
WINTERIZATION	Shut off water and drain down.
WARRANTY	One year warranty, labor not included.
SHIPPING WEIGHT	600 SM* 115 lbs. 600 SMSS* 115 lbs. *Meets ADA for High & Low 600 EZ WM* 50 lbs. 600 EZ WMSS* 50 lbs. 50 lbs. Sensor: 115 lbs. SE 600 SM* 115 lbs. SE 600 SMSS* 115 lbs. SE 600 EZ WM* 50 lbs. SE 600 EZ WMSS* 50 lbs. SE 600 EZ WM* 50 lbs.
	MOST DEPENDABLE FOUNTAINS, INC.™ 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587 www.mostdependable.com (901) 867-0039

LIMITED PRODUCT WARRANTY

Most Dependable Fountains, Inc.™

Most Dependable Fountains, Inc.[™] warrants that all of its products are guaranteed against defective material or poor workmanship for a period of one year from date of shipment. Most Dependable Fountains, Inc.™ liability under this warranty shall be discharged by furnishing without charge any goods, or part thereof, which shall appear to the Company upon inspection to be of defective material or not of first class workmanship. Most Dependable Fountains, Inc.[™] will not be liable for the cost of repairs, alterations or replacements, or for any expense connected therewith made by the owner or his agents. Most Dependable Fountains, Inc.[™] will not be liable for any damages caused by defective materials or poor workmanship, except for replacements, as provided above. Buyer agrees that Most Dependable Fountains, Inc.[™] has made no other warranties either expressed or implied in addition to those above stated. The products manufactured by Most Dependable Fountains, Inc.[™] is warranted to function if installation and maintenance instructions provided are adhered to. The units also must be used for the purpose for which they were intended.

