



## MDF 24-8 SMSS HYDRANT SPECIFICATIONS

### **STAINLESS STEEL PEDESTAL**

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

### **FAUCET**

Supplied with 3/4" anti-siphon vacuum breaker, frost resistant sill cock with removable handle.

### **RECESSED HOSE BIBB COVER**

This unit comes standard with a Recessed Hose Bibb with Locking Cover.

### **INSTALLATION**

**Surface Mount** installation, is designed to be anchored on top of a new or existing surface (concrete, etc.) For a new surface, a surface mount carrier is recommended. For an existing surface, anchor bolts are to be used through the attached mounting plate. Surface Mount Fountains come standard with an access door with vandal resistant stainless steel screws. Flush all new or existing supply lines prior to installation.

### **FINISH**

Oven baked powder coat. Choice of colors are:  green,  blue,  black,  red,  yellow,  orange,  brown and  white. Textured color choices:  emerald,  sapphire,  pyrite,  text-black,  burgundy,  gold vein,  copper and  sandstone. Stainless steel models are powder coated for added protection. The color  chrome is an available option for stainless steel models only.

### **WINTERIZATION**

Shut off water and drain down.

### **WARRANTY**

One year warranty, labor not included.

**MOST DEPENDABLE FOUNTAINS, INC.™**  
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)  
(901) 867-0039