Most Dependable Fountains, Inc.


OPERATIONS MANUAL

MODEL: MDF 36 DB & 36 DBSS

Most Dependable Fountains, Inc™ 5705 Commander Drive Arlington, TN 38002 901-867-0039 www.mostdependable.com



MOST DEPENDABLE FOUNTAINS, INC. 5705 COMMANDER DR. ARLINGTON, TN 38002-0587 PHONE: (901) 867-0039 www.mostdependable.com



NOTES:

- 1. ATTACHED VALVE BOX IS STANDARD ON ALL DIRECT BURY HYDRANTS/HOSE BIBBS.
- 2. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 3. DO NOT SCALE DRAWING.
- 4. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
- 5. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 3354-13.4.

MODEL 36 DB

DIRECT BURY WITH ATTACHED VALVE BOX



MDF 24 & 36 HYDRANT SPECIFICATIONS

STANDARD PEDESTAL	One piece weld construction with MDF standard 3/16" wall thickness.
OR STAINLESS STEEL PEDESTAL	One piece weld construction with MDF standard 304 schedule 10 stainless steel.
FAUCET	Supplied with 3/4" anti-siphon vacuum breaker, frost resistant sill cock with removable handle.
HOSE BIBB COVER	Optional locking hose bibb cover recommended.
INSTALLATION	Surface Mount installation, is designed to be anchored on top of a new or existing surface (concrete, etc.) For a new surface, a surface mount carrier is recommended. For an existing surface, anchor bolts are to be used through the attached mounting plate. Surface Mount Fountains come standard with an access door with vandal resistant stainless steel screws. 10" bury in ground for Direct Bury models. All direct bury models include an attached valve box with bolted cover. Flush all new or existing supply lines prior to installation.
FINISH	Oven baked powder coat. Choice of colors are: green, blue, blue, black, red, yellow, orange, brown and white. Textured color choices: merald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection. The color chrome is an available option for stainless steel models only.
WINTERIZATION	Shut off water and drain down.
WARRANTY	One year warranty, labor not included.

MOST DEPENDABLE FOUNTAINS, INC.™

5705 COMMANDER DR. • ARLINGTON, TN 38002-0587 www.mostdependable.com (901) 867-0039

INSTALLATION INSTRUCTIONS

Most Dependable Fountains, Inc.™

All **SM (surface mount)** products are designed to be installed on the surface of a new or existing concrete slab. Your contractor needs to provide a 1 ½" PVC drain line (**when applicable**) and water line thru finish grade. Connections are made to our SM products thru our access door, as shown on detail drawings. The water tubing is provided with a ½" male iron pipe connection. This is an excellent location for a cutoff valve. Surface Mount units are anchored to the existing concrete by means of ½" concrete shields with bolts or we recommend ½" quick bolts.

Note: We offer an <u>optional</u> template which is designed to be poured in the concrete slab. It comes with the necessary vandal resistant stainless steel bolts and washers needed to anchor.

All **DB** (**direct bury**) products are designed to be installed to a depth of 14" below grade. MDF provides 1 ½" PVC drain line inside the pedestal (**when applicable**) to point of connection by others. MDF also provides reinforced nylobraid flexible tubing with a ½" male iron pipe thread for connection to water supply by others. MDF recommends an optional valve box using a PVC conduit to the pedestal. By using this option you have complete control of your product.

Individual detail drawings available Online or by request.



For more information: Most Dependable Fountains, Inc.™ www.mostdependable.com Info@mostdependable.com 901-867-0039

LIMITED PRODUCT WARRANTY

Most Dependable Fountains, Inc.™


Most Dependable Fountains, Inc.[™] warrants that all of its products are guaranteed against defective material or poor workmanship for a period of one year from date of shipment. Most Dependable Fountains, Inc.™ liability under this warranty shall be discharged by furnishing without charge any goods, or part thereof, which shall appear to the Company upon inspection to be of defective material or not of first class workmanship. Most Dependable Fountains, Inc.[™] will not be liable for the cost of repairs, alterations or replacements, or for any expense connected therewith made by the owner or his agents. Most Dependable Fountains, Inc.[™] will not be liable for any damages caused by defective materials or poor workmanship, except for replacements, as provided above. Buyer agrees that Most Dependable Fountains, Inc.[™] has made no other warranties either expressed or implied in addition to those above stated. The products manufactured by Most Dependable Fountains, Inc.[™] is warranted to function if installation and maintenance instructions provided are adhered to. The units also must be used for the purpose for which they were intended.





Powder Coating Color Chart

SMOOTH: Available for Standard & Stainless Steel Units.



TEXTURED: Available for Standard & Stainless Steel Units.



Textured Pyrite

Textured Sandstone

Textured Gold Vein

Textured Copper

CHROME: Available for Stainless Steel Units Only.



Colors on computer monitors vary greatly. Please request a color card or paint sample.

Chrome