



# Bike Rinse Station Specifications

STANDARD PEDESTAL  
OR  
 STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

CONTROL VALVE

Requires less than 5 lbs to operate. Slow closing metered valve. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing — **this tubing is not plastic**. It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection. Supply line stops above grade. Water Filter is standard on this model.

FINISH

**Oven baked powder coat color choices:**

- Green,  Blue,  Black,  Red,  Brown,  White,  Teal,  Umbria Grey

**Textured color choices:**

- Emerald,  Sapphire,  Textured Black,  Pyrite,  Sandstone,  Gold Vein,  Copper

**The color CHROME is an available option for Stainless Steel (SS) models only.**

- Chrome

\*Stainless steel models are powder coated for added protection.\*

INSTALLATION

Surface Mount installation is designed to be anchored on top of a new or existing surface (concrete, etc.) For a new surface, anchor bolts are to be used through the attached mounting plate. Surface Mount Fountains come standard with an access door with vandal resistant stainless steel screws.

WINTERIZATION

Shut off water and drain down.

WARRANTY

One year warranty, labor not included.

SHIPPING WEIGHT

Model 150 SM ..... 140 lbs  
Model 150 SMSS ..... 140 lbs

