



# FOOT & SHOWER TOWER SERIES SPECIFICATIONS

## STANDARD PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

OR

## STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

## PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

## SPRAY HEADS

1.5 GPM at 60 PSI.

## CONTROL VALVE

Requires less than 5 lbs to operate. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.

## WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing - **this tubing is not plastic**. It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection. Supply line stops above grade.

## INSTALLATION

**Surface Mount** installation, is designed to be anchored on top of a new or existing surface (concrete, etc.) For a new surface, a surface mount carrier is recommended. For an existing surface, anchor bolts are to be used through the attached mounting plate. Surface Mount Fountains come standard with an access door with vandal resistant stainless steel screws.

## FINISH

Oven baked powder coat. Choice of colors are:  green,  blue,  black,  red,  yellow,  orange,  brown and  white. Textured color choices:  emerald,  sapphire,  pyrite,  text-black,  burgundy,  gold vein,  copper and  sandstone. Stainless steel models are powder coated for added protection. The color  chrome is an available option for stainless steel models only.

## WINTERIZATION

Shut off water and drain down.

## WARRANTY

One year warranty, labor not included.

## SHIPPING WEIGHT

Model 500 SM.....	100 lbs	Model 550 SM.....	170 lbs	Model 575 SM.....	155 lbs
Model 500 SMSS....	100 lbs	Model 550 SMSS.....	170 lbs	Model 575 SMSS...	155 lbs
Model 500 WM.....	120 lbs	Model 564 SM.....	160 lbs	Model 580 SM.....	200 lbs
Model 500 WMSS...	120 lbs	Model 564 SMSS.....	160 lbs	Model 580 SMSS...	200 lbs
Model 525 SM.....	45 lbs	Model 565 SM.....	185 lbs	Model 590 SM.....	175 lbs
Model 525 SMSS.....	45 lbs	Model 565 SMSS.....	185 lbs	Model 590 SMSS...	175 lbs
Model 552 SM.....	200 lbs	Model 552 SMSS.....	200 lbs		

Above specifications apply with these notes:

Model 500 - One shower & one foot spray.

Model 525 - Foot Tower: one head only.

Model 550 - One shower, one foot spray & accessible drinking fountain.

Model 552 - One shower, one foot spray with both high & low ADA drinking fountains.

Model 564 - Accessible shower with one metered head at 72" & a foot wash on one side & one metered accessible head at 49" on back side, with 2 grab bars.

Model 565 - Accessible shower with one metered head at 72", one metered head at 49" & a non-metered foot wash (on same side) with 2 grab bars.

Model 575 - Dual (back to back) shower & foot spray heads.

Model 580 - One shower, one foot spray & trough style accessible drinking fountain.

Model 590 - Four shower heads & one foot spray.

Model 500-8 - Denotes custom: call for more information.

**MOST DEPENDABLE FOUNTAINS, INC.™**  
 5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)  
 (901) 867-0039

