



## FUNTIME SHOWER SPECIFICATIONS

### ■ STANDARD PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

OR

### ■ STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

### PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

### SPRAY HEADS

Four upward shower sprayheads.

### CONTROL VALVE

Requires less than 5 lbs to operate. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI. Two slow closing metered valves can be set to run from 30 to 45 seconds before shutting off. Once valve controls 2 spray heads that cover a 9' half radius.

### INSTALLATION

**Surface Mount** installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the unit. Surface mount carrier recommended for all surface mount installations. Access door standard on all pedestal units.

### FINISH

Oven baked powder coat. Choice of colors are:  green,  blue,  black,  red,  yellow,  orange,  brown and  white. Textured color choices:  emerald,  sapphire,  pyrite,  text-black,  burgundy,  gold vein,  copper and  sand-stone. Stainless steel models are powder coated for added protection. The color  chrome is available for stainless steel models only.

### WINTERIZATION

Shut off water and drain down. Remove valve during winter months.

### WARRANTY

One year warranty, labor not included.

### SHIPPING WEIGHT

130 lbs.

**MOST DEPENDABLE FOUNTAINS, INC.™**  
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)