



BIKE REPAIR SPECIFICATIONS

WATER QUALITY (LEAD FREE)

Section 9, California Proposition 6 and the Federal Safe Drinking Water Act.*

■ STANDARD PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

OR

■ STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

BOTTLE FILLER SPOUT

Sanitary recessed nozzle.*

PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.*

CONTROL VALVE

Requires less than 5 lbs to operate. Non-cartridge O-ring valve delivers steady stream of water through an adjustable valve. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI.*

CABLES

3/16" Stainless Steel braided cables.

TOOLS

(1) Phillips Screw Driver, (1) Standard Screw Driver, (1) 6" Crescent Wrench, (1) 10" Crescent Wrench, (1) Metric Hex Key Set, (2) Lever Tire Tools & (7) Stainless Steel Cable Assembly

AIR PUMP

Working parts encased in stainless steel shaft.

AIR HOSE

Braided stainless steel with dual air chuck.

WATER SUPPLY (LEAD FREE)

Maintenance free reinforced nylobraid tubing - **this tubing is not plastic**. It is supplied with a 1/2" MIP threaded inlet with stainless steel strainer. Union fittings at every connection. Supply line stops above grade. Water Filter is standard on this model.*

DRAIN

1 1/2" schedule 40 PVC pipe. Drain line stops above grade.*

FINISH

Oven baked powder coat. Choice of colors are: green, blue, black, red, yellow, orange, brown and white. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sandstone. Stainless steel models are powder coated for added protection. The color chrome is an available option for stainless steel models only.

INSTALLATION

Surface Mount installation, is designed to be anchored on top of a new or existing surface (concrete,etc.) For a new surface, a surface mount carrier is recommended. For an existing surface, anchor bolts are to be used through the attached mounting plate. Surface Mount Fountains come standard with an access door with vandal resistant stainless steel screws.

WINTERIZATION

Shut off water and drain down. Remove water filter.*

WARRANTY

One year warranty, labor not included.

SHIPPING WEIGHT

Model 185 SM..... 200 lbs Model 195 SM*..... 130 lbs
Model 185 SMSS..... 200 lbs Model 195 SMSS*.... 130 lbs

MOST DEPENDABLE FOUNTAINS, INC.™
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com
(901) 867-0039

