



# MDF PLAY SPRAY 1 SM SPECIFICATIONS

## **PEDESTAL**

One piece weld construction with MDF standard 3/16" wall thickness **or optional** 304 schedule 10 stainless steel.

## **IN-GROUND OUTLETS**

2 in-ground outlet spray heads controlled from one remote pedestal.

## **VALVE**

Valve is metered and can be set to run 45 seconds.

## **WATER PATTERN**

At 60 PSI, the circular water pattern is 10' diameter for each outlet.

## **INSTALLATION**

The **Play Spray** pedestal is designed to be anchored to a concrete slab by means of our 8" template that is set in concrete. Stainless Steel Surface Carrier included. The in-ground water outlets design is to be flush and anchored to a concrete slab.

## **WINTERIZATION**

Shut off water and drain down.

## **SUPPLY LINE**

3/4" water inlet and outlet.

## **FINISH**

Oven baked powder coat. Choice of colors are: green, blue, brown, black, red, yellow, orange, white and chrome. Textured color choices: emerald, sapphire, pyrite, text-black, burgandy, gold vein, copper and sandstone. Play Sprays are powder coated for added protection and all colors listed are available.

## **SHIPPING WEIGHT**

40 lbs.

**MOST DEPENDABLE FOUNTAINS, INC.™**  
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008  
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587  
[www.mostdependable.com](http://www.mostdependable.com)