



PLAY TOWER SPECIFICATIONS

■ STANDARD PEDESTAL

One piece weld construction with MDF standard 3/16" wall thickness.

OR

■ STAINLESS STEEL PEDESTAL

One piece weld construction with MDF standard 304 schedule 10 stainless steel.

PUSH BAR

304 stainless steel with circumference exceeding 8.6". Mushroom style push bar overlaps and prevents sand and other objects from sticking push bar in the ON position. Stainless steel bubbler housing standard.

SPRAY PATTERNS

Please refer to written product descriptions below.

CONTROL VALVE

Requires less than 5 lbs to operate. This valve design is to operate and function at 30 to 80 PSI. Ideal operating pressure is 60 PSI. One valve with an approximate run time of 30 to 40 seconds.

INSTALLATION

Surface Mount installation, is designed to be anchored on top of an existing surface (concrete, etc.) with anchor bolts through a mounting plate that is welded to the unit. Surface mount carrier recommended for all surface mount installations. Access door standard on all pedestal units.

FINISH

Oven baked powder coat. Choice of colors are: green, blue, black, red, yellow, orange, brown and white. Textured color choices: emerald, sapphire, pyrite, text-black, burgundy, gold vein, copper and sand-stone. Stainless steel models are powder coated for added protection. The color chrome is available for stainless steel models only.

WINTERIZATION

Shut off water and drain down. Remove valve during winter months.

WARRANTY

One year warranty, labor not included.

SHIPPING WEIGHT

Play Tower 1 SM..... 185 lbs. Play Tower 2 SM..... 55 lbs. Play Tower 3 SM. 130 lbs.
Play Tower 1 SMSS..... 185 lbs. Play Tower 2 SMSS.. 55 lbs. Play Tower 3 SMSS.. 130 lbs.

Above specifications apply with these notes:

Play Tower 1 - Pedestal Play Tower provides a 42" cascading shower effect.

Play Tower 2 - Pedestal Play Tower provides an upward spray of 20'.

Play Tower 3 - Pedestal Play Tower mimics a candy cane shape with a 40" x 40" spray projecting 6'.

MOST DEPENDABLE FOUNTAINS, INC.™
(800) 552-6331 • (901) 867-0039 • Fax (901) 867-4008
5705 COMMANDER DR. • ARLINGTON, TN 38002-0587
www.mostdependable.com